

## Mechanical Power Press



H FRAME  
PNEUMATIC CLUTCH & BRAKE



# H Type Power Press

## Technical Specification

Discription	SHPP10	SHPP20	SHPP30	SHPP50	SHPP75	SHPP100	SHPP150	SHPP200	SHPP250
Ton Capacity	10	20	30	50	75	100	150	200	250
Crank Shaft dia	60	76	83	102	114	134	152	158	165
Stroke Length	51	63	75	102	114	127	140	152	165
Stroke Adjustment	6-51	13-63	13-75	13-102	13-114	13-127	13-140	13-152	13-165
Slide Adjustment	25	40	40	50	60	60	70	70	75
Bed Size LxW	355x460	457x508	508x559	559x610	610x762	660x813	711x914	762x965	812x1016
Hole in Bed	76	89-108	102-127	127-152	178-203	191-216	216-241	229-254	229-254
Distance Bed to Ram	203	254	292	356	380	406	457	495	519
Distance Bolster Plate to Ram	254	314	362	441	470	496	557	595	629
Stroke Per Minute	80	55	40	30	30	30	30	30	25
Table Height	725	762	762	813	813	890	890	890	890
Fly Wheel Diameter	406	533	609	700	810	924	1016	1150	1320
Geared Diameter	355	460	533	635	812	864	1016	1120	12995
Motor HP	1	2	3	5	7.5	10	15	20	25
Approx Weight in kgs.	500	900	1200	2100	3500	4600	5600	8800	11000
Overall Dimension (LxWxH)	1100x800x1600	1200x900x1850	1300x1050x2000	1500x1400x2500	1700x1600x3000	1800x1850x3100	2000x2100x3200	2200x2250x3300	2300x2230x3400

### Standard Features:

- Die Clamp
- Pulley
- Stud Driver
- Tie Rod
- Motor Stand
- Manual Lubrication System
- Knock-out System
- Fly wheel & Gear Guard
- Oil Cups for Lubrication Point

### Optional Accessories:

- Motor Starter
- Electric Motor
- V-Belt
- Stroke Counter
- Foundation Bolt

### Model :

- 'C' Frame Machine
- 'H' Frame Machine
- 'C' Frame Inclinable type Machine
- Single Geared Drive
- Double Geared Drive
- Un-Geared Drive